

K26 TYPE -40°C +85°C 12000H

RoHS Compliant

- Surge-proof capacitor in aluminium can with insulation sleeve.
- Snap in terminals for PCB mounting.
- Design optimized for high ripple current applications.




APPLICATIONS

Designed for professional application.
Ultra compact UPS, Solar inverters, High ripple current converters, Motor drives.

Dimensions in mm.

Circuit board hole dimensions




2 PIN CAPACITOR






PIN LENGTH

P 4.5 short pin - P 6.3 long pin (standard)




3 PIN CAPACITOR



4 PIN CAPACITOR



5 PIN CAPACITOR



Ø	22	25	30	35	40	45	50
2 PIN	●	●	●	●	●		
3 PIN		●	●	●			
4 PIN				●	●	●	●
5 PIN					●		

On demand, only for capacitors with diam ≥ 35mm: octagonal can shape for long stress vibration applications.

SPECIFICATIONS

Temperature Range	Operating: -40°C +85°C [Environmental classification 40/85/56 IEC-68] Storage : Preferably below +25°C, not exceeding +40°C							
Rated Voltage Range (V_r)	from 400V to 500V DC							
Surge Voltage (V_p)	V _p = 1.10 V _r							
Rated Capacitance Range	from 1000 µF to 2700 µF							
Capacitance Tolerance	±20% at 100 Hz, 20°C [M class IEC-62] on request: -10% +30% at 100 Hz, 20°C [Q class IEC-62]							
Leakage Current (I_L) (mA, 5 min, 20°C)	max I _L = 0.006 C _r V _r + 4 µA At 85°C max I _L = 0.04 C _r V _r µA		Kendeil product limit: I _L = 0.003 C _r V _r					
Ripple current (I_r)	Refer to table at 85°C and 100Hz:							
	FREQUENCY MULTIPLIER	50Hz 0.88	100Hz 1.0	500 Hz 1.45	1000Hz 1.50	>10kHz 1.55		
	AMBIENT TEMP. MULTIPLIER	35°C 2.2	45°C 2.1	55°C 1.8	65°C 1.6	75°C 1.4	85°C 1.0	95°C 0.5
	Maximum internal temperature	98°C						
Insulation Resistance	At 100V DC for 1 min is >100 MΩ across insulating sleeve and terminals.							
Vibration Resistance	Frequency range: 10 Hz to 500 Hz, amplitude 0.75 mm max acceleration 10g for 3x2 h							
Withstand voltage (between terminals bundled and plate)	2500 VAC for 1 min							
Life test	After 2,000 hours application of rated voltage at 85°C capacitors meet characteristics aside		Cap change tan δ Leakage current (I _L) Impedance (Z)	≤ 10% ≤ 130% < initial limit ≤ 200%				
Shelf life	After leaving capacitors under no load for 500 hours at 85°C, when restored at 20°C meet specifications aside		Cap change tan δ Leakage current (I _L)	≤ ±15% ≤ 150% < initial limit				
Useful life (V_n, Temp rated I ripple applied)	> 200000 h at 40°C > 12000 h at 85°C							
Failure percentage Failure rate	≤ 1% (during useful life) ≤ 33 fit (33 10 ⁻⁹ /h)							
Self inductance	Approx. 20 nH							
Damp heat test (V_n applied, 2000 hours, 85% RH)	Stable electrical parameters in humidity ambient condition 85°C							
Electrolyte	All the capacitors of this series have self-extinguishing electrolyte in accordance with IEC EN 60695-11-10							
Marking information	minus pole band aside within an angle of 41° ± 25°							
Reference standards	CECC 30.300 - IEC 60384-4 LONG LIFE GRADE							

K26 TYPE STANDARD RATINGS

Cap μF	$\varnothing \times L$ mm	Tan δ MAX 100 Hz 20°C	ESR TYP m Ω 100 Hz 20°C	Z TYP m Ω 10 kHz 20°C	I _r a.c. A max 100 Hz 85°C	PART NUMBER termination digit excluded
1000	40x60	0.12	99	74	5.1	K26400102_PM0F060
1200	40x77	0.12	94	64	5.2	K26400122_PM0F077
1500	45x60	0.12	84	61	5.4	K26400152_PM0N060
1800	45x77	0.12	70	51	6.2	K26400182_PM0N077
1800	50x60	0.10	70	51	6.5	K26400182_PM0V060
2000	40x105	0.12	61	44	7.6	K26400202_PM0F105
2200	45x105	0.13	47	40	7.8	K26400222_PM0N105
2200	50x77	0.10	47	40	7.6	K26400222_PM0V077
2700	45x105	0.13	46	39	9.2	K26400272_PM0N105
3300	50x105	0.10	37	30	10.2	K26400332_PM0V105

**RATED
VOLTAGE
VDC**

400V

Cap μF	$\varnothing \times L$ mm	Tan δ MAX 100 Hz 20°C	ESR TYP m Ω 100 Hz 20°C	Z TYP m Ω 10 kHz 20°C	I _r a.c. A max 100 Hz 85°C	PART NUMBER termination digit excluded
1000	40x60	0.11	99	74	5.1	K26420102_PM0F060
1200	40x77	0.11	94	64	5.2	K26420122_PM0F077
1200	45x60	0.11	94	64	5.2	K26420122_PM0N060
1500	40x105	0.12	75	55	6.3	K26420152_PM0F105
1500	45x77	0.12	75	55	5.6	K26420152_PM0N077
1500	50x60	0.10	75	55	5.7	K26420152_PM0V060
1800	50x77	0.10	67	50	6.9	K26420182_PM0V077
2200	45x105	0.13	47	40	7.8	K26420222_PM0N105
2700	50x105	0.10	37	30	9.5	K26420272_PM0V105

**RATED
VOLTAGE
VDC**

420V

Cap μF	$\varnothing \times L$ mm	Tan δ MAX 100 Hz 20°C	ESR TYP m Ω 100 Hz 20°C	Z TYP m Ω 10 kHz 20°C	I _r a.c. A max 100 Hz 85°C	PART NUMBER termination digit excluded
1000	40x60	0.11	99	74	5.1	K26450102_PM0F060
1200	40x77	0.11	94	64	5.2	K26450122_PM0F077
1200	45x60	0.11	94	64	5.2	K26450122_PM0N060
1500	40x105	0.12	75	55	6.3	K26450152_PM0F105
1500	45x77	0.12	75	55	5.6	K26450152_PM0N077
1500	50x60	0.10	75	55	5.7	K26450152_PM0V060
1800	50x77	0.10	67	50	6.9	K26450182_PM0V077
2200	45x105	0.13	47	40	7.8	K26450222_PM0N105
2700	50x105	0.10	37	30	9.5	K26450272_PM0V105

**RATED
VOLTAGE
VDC**

450V

PLEASE TO CONTACT OUR TECHNICAL SERVICE FOR MORE INFORMATION OR SPEC-IN ANALYSIS.

K26 TYPE STANDARD RATINGS


Cap μF	$\varnothing \times L$ Mm	Tan δ MAX 100 Hz 20°C	ESR TYP $m\Omega$ 100 Hz 20°C	Z TYP $m\Omega$ 10KHz 20°C	Ir a.c. A max 100 Hz 85°C	PART NUMBER Termination digit excluded
330	35x40	0.12	250	180	2.2	K26500331_PM0E040
470	35x50	0.12	187	153	2.6	K26500471_PM0E050
560	40x50	0.12	176	134	3.1	K26500561_PM0F050
560	35x60	0.12	176	134	3.2	K26500561_PM0E060
680	35x77	0.12	165	120	3.8	K26500681_PM0E077
680	40x60	0.12	165	120	3.8	K26500681_PM0F060
820	40x77	0.12	138	108	4.7	K26500821_PM0F077
1000	40x97	0.12	115	95	6.0	K26500102_PM0F097
1500	45x97	0.12	90	80	7.1	K26500152_PM0N097
1700	45x105	0.12	77	72	7.3	K26500172_PM0N105

**RATED
VOLTAGE
VDC**

500V

PART NUMBER SYSTEM FOR SNAP-IN TYPE CAPACITORS

New PART-NUMBER CODE in use since Sep 2010. Total length is 17 digits.
Please see examples below and have a reference code from the standard ratings capacitors pages.



EXAMPLES

K	0	5	4	5	0	4	7	1	0	P	M	0	E	0	5	0
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

K05 450V 470µF, standard pin, ±20%, 35x50

Specifications subject to change without notice